

Model Number	OC300(UN)1.0
HARDWARE FEATURES	
Interface	<ul style="list-style-type: none"> • 2× 10/100/1000 Mbps Ethernet Ports • 1× USB 3.0 Port
Power Supply	100–240 V~50/60 Hz, 0.6 A
Dimensions	11.6 × 7.1 × 1.7 in (294 × 180 × 44 mm)
MANAGEMENT	
Omada App	Yes
Centralized Management	<ul style="list-style-type: none"> • Up to 500 Omada access points, 100 JetStream switches, and 100 Omada routers* • Up to 15,000 clients <p>*Only some JetStream switches and Omada routers can be centrally managed by OC300, please refer to www.tp-link.com/business-networking/all-omada/ to find all the models supported by OC300</p>
Cloud Access	Yes
L3 Management	Yes
Multi-site Management	Yes
Management Features	<ul style="list-style-type: none"> • Automatic Device Discovery • Batch Configuration • Batch Firmware Upgrading • Intelligent Network Monitoring • Abnormal Event Warnings • Unified Configuration • Reboot Schedule • Captive Portal Configuration
OTHERS	
Certification	CE, FCC, RoHS
Package Contents	<ul style="list-style-type: none"> • Omada Hardware Controller OC300 • Quick Installation Guide • Ethernet Cable • Power Cord • Rackmount Kit
System Requirements	Microsoft® Windows®10, 8, 7, Vista™, XP or MAC® OS, NetWare®, UNIX® or Linux
Environment	<ul style="list-style-type: none"> • Operating Temperature: 0–50 °C (32–122 °F) • Storage Temperature: -40–70 °C (-40–158 °F) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing